

WEB: www.kelberg.no

UNIVERSAL TRANSPORT & FLYTTEFORRETNING **KEL-BERG** NELEDENG

MODEL S601H

KEL-BERG 3 AXLE PULL-OUT TRAILER, SHORT VERSION FOR CRANE TRUCKS

SPECIFICATION

KEL-BERG 3 AXLE PULL-OUT TRAILER, SHORT VERSION FOR CRANE TRUCKS

DIMENSIONS & WEIGHTS:

Block lorry:

Permissible gross vehicle weight Permissible main bolt load Permissible bogie load

Extended chassis length Wheelbase Bogie Lowered part Landing Coupling height Overhang Outside width Bottom height in rear Neck length 48,000kg 18,000 kg 30,000 kg

10,319 mm + extension 4,500 mm 5,699 mm 2 x 1,310 mm 6,620 mm 4,100 mm 1,350 mm 1,000 mm 2,550 mm 930 mm 3,699 mm







CHASSIS:

Centre beam in welded high-strength steel where the sections slide inside each other. Heavy-duty chassis that is suitable for heavy-duty applications. U-rail on the neck bend for the installation of aluminium ramps.

PAINTING:

Sandblasted for SA 2.5 2-component primer and 2-component final coat. Chassis painted in EN RAL colour in approved ICI products.

AXLES:

3 x 11 tonne SAF axles with drum brakes. Co-steering swivelling 3rd axle that can be locked above tail lights. 3rd axle is liftable.

WWW.KELBERG.NO | INFO@KELBERG.NO

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Norge accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. E&OE.



SPECIFICATION

KEL-BERG 3 AXLE PULL-OUT TRAILER, SHORT VERSION FOR CRANE TRUCKS

TYRES:

Fitted with 16 pcs. 205/65R17.5 tyres of a recognised brand.

BRAKES:

2-line compressed air mechanical brake system with 80L steel tank in black. Spring brake mounted on 2 axles with release valve mounted in the left rear. ABS brake system brand Knorr/WABCO for 2S/2M

KINGPIN:

2" SAE kingpin.

LANDING LEGS:

2 landing legs of recognised brand with two speeds and S-foot. 2 pcs. swivelling/extendable landing legs in the rear, manually operated.

SIDES:

400mm steel front and removable 400mm aluminium sides on landing.

LOAD SECURING:

- 8 pairs of heavy-duty tie rods in 50kn edge frame
- 8 pairs of 80 x 50mm plinths in edge rail

ELECTRICAL SYSTEM:

The electrical system is manufactured according to ISO 3731. It features:

- 2 pcs. 5-chamber rear lights
- 2 no. plate lights
- 2 x swivelling lights
- 5 side marker lights with reflector per side, statutory marker lights and statutory reflectors
- 2 x 7-pin light sockets

FLOOR:

Landing: 28 mm wooden planks, with steel door over king pin.

PAGE: 3

WWW.KELBERG.NO | INFO@KELBERG.NO

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Norge accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. E&OE.