



MODEL
T560K

KEL-BERG 4-AXLE 38T DRAWBAR
ALUMINIUM TIPPING TRAILER

TRAILER SPECIFICATION

KEL-BERG 4-AXLE 38T DRAWBAR ALUMINIUM TIPPING TRAILER

DIMENSIONS & WEIGHTS:

Axle Speed: 90 km/h
Front axle load: 18,000 kg
Rear axle load: 20,000 kg
Total weight: 38,000 kg
Tare weight: 7,000 kg

Overall length: 13,380 / 15,080 / 15,600 mm
Coupling height: 3,400 / 4,900 / 5,400 mm
Front overhang: 770 mm
Rear overhang: 1,350 mm
Coupling height: 650 mm
Coupling width: 2,500 mm


Wheelbase: 1,130 / 4,940 / 1,810 mm
Internal length: 8,900 mm
Internal width: 2,440 mm
Internal height: 1,350 mm
Approximate cubic capacity: 30 m³
Tilt angle: 46 degrees

CHASSIS:

Constructed from heavy duty welded frame with drag from Trako.

AXLES:

Fitted with 2 x 9 ton BPW disc brake axles front, 2 x 10 ton BPW disc brake axles rear. Features air suspension with level control valve for front and rear, ABS and EBS. 4th axle is liftable via switch in the vehicle.



TRAILER SPECIFICATION

KEL-BERG 4-AXLE 38T DRAWBAR ALUMINIUM TIPPING TRAILER

BRAKES:

2 line compressed air system with EBS and ABS. Spring brake bells for parking brake. 1 piece duomatic red / yellow.

WHEELS & TYRES:

Fitted with 8 pcs 385/65R22.5 tyres mounted on aluminium Alcoa Durabright rims M+S.

ELECTRICAL SYSTEM:

- 24 volts according to applicable regulations
- 3 x 3 multi-chamber rear lights
- 6 pcs. LED work lights
- 2 work lights in the tipper box

ELECTRICAL CONNECTORS:

Fitted with 14-pin VBG connector for lighting.

TIPPING BODY:

Body constructed from aluminium. Approximate capacity 30 m³. 7 mm floor, 5 mm sides. Lifted with Penta tipping cylinder – Max 170 bar.

PAINTING:

Chassis is painted in optional RAL colour. Aluminium body painted in optional RAL colour.

WARRANTY:

12 months factory warranty.

MISCELLANEOUS:

- Reflective tape in accordance with (ECE70) at the rear
- Red/white contour markings on sides and rear
- Skermar with anti-spray
- 2 pcs. weight clocks Ananloge
- 2 pcs. rear flashing lights
- 1 large Kel-Berg rear mudflap
- Plastic on rear underrun barrier
- Springs on the hitch

